



HYMER

HYMER

THE HIGHEST CLASS

HYMER ladders with R13 anti-slip surface – highest safety standards in demanding working environments.

STEP LADDER R13 WITH PLATFORM, SINGLE-SIDED ACCESSIBLE

- Work safety in the highest slip resistance class R13. Suitable for use in oily areas.
- Ergonomic working on 80 mm step depth. Front step edges flush with stile.
- Comfortable and safe standing for longer periods of work thanks to the large platform.
- Solid aluminium storage tray with bucket hook.
- High-strength perlon straps provide reliable safety strut.

Features:

- R13 coating on the entire step surface.
- Screw-in ladder feet.
- Platform dimensions 250 x 250 mm.
- According to EN 131.



862606

Number of steps incl. platform	4	5	6	7	8	10	12	14
Stile (approx. mm)	71	71	71	71	71	71	71	71
Length (approx. m)	1.70	1.95	2.20	2.45	2.70	3.20	3.70	4.20
Standing height (height to platform) (approx. m)	0.93	1.16	1.40	1.63	1.85	2.32	2.78	3.25
Reach height (approx. m)	2.93	3.16	3.40	3.63	3.85	4.32	4.78	5.25
Vertical height (approx. m)	1.55	1.78	2.01	2.25	2.48	2.94	3.40	3.87
Width top/bottom (approx. mm)	305/480	305/500	305/530	305/550	305/570	305/630	305/680	305/740
Base width (approx. m)	0.90	1.05	1.20	1.35	1.50	1.85	2.20	2.55
Weight (approx. kg)	6.3	7.3	8.3	9.5	10.6	13.1	15.3	18.3
Spreader lock (perlon strap)	-	-	-	✓	✓	✓	✓	✓
Order no.	862604	862605	862606	862607	862608	862610	862612	862614

STEP LADDER R13, DOUBLE-SIDED ACCESSIBLE

- Work safety in the highest slip resistance class R13.
Suitable for use in oily areas.
- Ergonomic working on 80 mm step depth.
Front step edges flush with stile.
- Torsion-resistant, cast aluminium hinges.
- High-strength perlon straps provide reliable safety strut.

Features:

- R13 coating on the entire step surface.
- Screw-in ladder feet.
- According to EN 131.



Number of steps	2x3	2x4	2x5	2x6	2x7	2x8	2x9	2x10	2x12
Stile (approx. mm)	71	71	71	71	71	71	71	71	71
Length (approx. m)	0.77	1.04	1.30	1.53	1.80	2.05	2.28	2.54	3.04
Standing height (approx. m)	0.22	0.45	0.69	0.92	1.15	1.38	1.61	1.85	2.31
Reach height (approx. m)	2.22	2.45	2.69	2.92	3.15	3.38	3.61	3.85	4.31
Vertical height (approx. m)	0.70	0.95	1.15	1.40	1.65	1.85	2.10	2.30	2.80
Width top/bottom (approx. mm)	355/430	355/450	355/475	355/500	355/525	355/550	355/575	355/600	355/650
Base width (approx. m)	0.80	0.98	1.15	1.30	1.50	1.70	1.95	2.15	2.50
Weight (approx. kg)	4.8	6.2	7.6	9.1	10.5	12.1	13.6	15.3	18.7
Order no.	862406	862408	862410	862412	862414	862416	862418	862420	862424

STEP LEANING LADDER R13

- Work safety in the highest slip resistance class R13.
Suitable for use in oily areas.
- Ergonomic working on 80 mm step depth.
Front step edges flush with stile.
- Very robust thanks to torsion-resistant,
swaged stile/step connection.
- More ground clearance and stability thanks
to the arched cross-beam.
- Convenient, ergonomic ladder width.

Features:

- **R13 coating on the entire step surface.**
- **Inner ladder width 370 mm.**
- **According to EN 131.**



A Bolted ladder feet
B Curved cross-beam



Number of steps	8	10	12	14	16
Stile (approx. mm)	71	71	71	71	71
Length (approx. m)	2.22	2.72	3.22	3.72	4.22
Standing height (approx. m)	1.17	1.63	2.09	2.56	3.02
Reach height (approx. m)	3.17	3.63	4.09	4.56	5.02
Width top/bottom (approx. mm)	425/425	425/425	425/961	425/961	425/961
Weight (approx. kg)	6.3	7.7	10.2	11.3	13.3
Ladder bottom	A	A	B	B	B
Order no.	891208	891210	891212	891214	891216

PLATFORM LADDER R13 WITH TIP AND ROLL WHEELS AND LONG HANDRAIL

- Work safety in the highest slip resistance class R13. Suitable for use in oily areas.
- Ergonomic working on 80 mm step depth. Front step edges flush with stile.
- Solid aluminium storage tray with bucket hook.
- Detachable, rigid brace prevents accidental folding.
- Ergonomically shaped handrails on both sides.
- Conical design ensures ladder stability.

Features:

- R13 coating on the entire step surface.
- Platform dimensions 440 x 400 mm.
- Guardrail height above platform 800 mm.
- According to EN 131.



Number of steps incl. platform	4	5	6	7	8	9	10	12
Stile (approx. mm)	71	71	71	71	71	71	71	71
Length (approx. m)	1.95	2.20	2.45	2.70	2.95	3.20	3.45	3.95
Standing height (height to platf.) (approx. m)	0.95	1.15	1.40	1.65	1.85	2.10	2.35	2.80
Reach height (approx. m)	2.95	3.15	3.40	3.65	3.85	4.10	4.35	4.80
Vertical height (approx. m)	1.75	2.00	2.20	2.55	2.70	3.00	3.15	3.60
Width (approx. mm)	650	670	700	730	750	780	800	850
Base width (approx. m)	1.15	1.30	1.45	1.60	1.75	1.90	2.05	2.35
Weight (approx. kg)	11.7	12.9	14.2	16.2	17.6	18.5	19.8	24.5
Spreader lock (rigid brace)	-	-	-	-	✓	✓	✓	✓
Order no.	868104	868105	868106	868107	868108	868109	868110	868112

Hymer-Leichtmetallbau GmbH & Co. KG

Käferhofen 10 | 88239 Wangen | Germany

Telephone +49 75 22 700-700

international-sales@hymer-alu.de | hymer-access.com